



Xstream® GG40® Antifreeze & Coolant Concentrate

Glystantin® GG40® by BASF is approved by:

Audi/Bentley/Bugatti/Lamborghini/Seat/Skoda/VW vehicles as from 2011 (TL 774-J).

This Engine Coolant Concentrate conforms to the requirements of: BS 6580:2010.

Product Features:

- Ethylene glycol and glycerine based antifreeze with advanced silicate inhibitors (Si-OAT).
- Protects against corrosion, overheating and freezing.
- Typical service life of up to 5 years.
- Safeguarded with bittering agent to help prevent accidental ingestion.
- To ensure correct antifreeze & coolant selection check Comma's latest application guide in store or online at www.CommaOil.com.

Directions for use:

1. Dilute with de-ionised water in accordance with the vehicle manufacturer's instructions.
2. Pour into vehicle cooling system.
3. Do not mix different types of Antifreezes. If in doubt about product suitability, refer to vehicle handbook.
4. Remove spills from paintwork immediately.

Handling:

- Minor spills should be soaked up with oil absorbent granules, sand or dirt. The spillage site should then be washed with soapy water and dried.
- Wash off any spillage on paintwork immediately.
- Avoid galvanised containers for storage or dispensing as they will corrode and contaminate the product.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD

Typical Inspection Data:

Density @ 20 °C	1.152 g/cm ³
Appearance	Clear Violet liquid
Boiling point	184 °C
Reserve Alkalinity	9ml
Water Content	2.6%
Refractive Index	1.442

Protection Levels:

Xstream® GG40® (%)	Approx. Protection (°C)
33	-16
50	-35