

## **Technical** Data Sheet



Typical Inspection Data:	
Density @ 20 °C	0.840 g/cm <sup>3</sup>
Viscosity @ 100 °C	7.3 cSt
Viscosity @ 40 °C	36 cSt
Phosphorus	0.02%
Colour	Brown
Pour Point	-36 °C

#### **Performance Profile:**

Recommended by Comma for certain DSG and DCT transmissions. Suitable for use where the following specifications are called for:

BMW Drivelogic 7-speed (Getrag) DCTF-1, BMW 6-Speed DCT, BMW MTF LT-5	Borg Warner
Bugatti Veyron	Castrol BOT 341
Chrysler 68044345 EA & GA, Powershift 6-speed Getrag	DCT-1
Ferrari 7-speed (Getrag)/TE DCT-3	Ford/Nissan Powershift 6-speed (GFT) / Ford WSS-M2C936A, Part # 1490763/1490761, WSS-M2C200-D2 / XT-11-QDC
Mitsubishi TC-SST 6-speed (GFT) / MZ320065 Dia Queen SSTF-1	Pentosin FFL 2, FFL 3, FFL 4
Peugeot/Citroen DCS 6-speed (GFT)/9734.S2	Renault EDC 6-speed (Getrag)
Shell TF DCT-F3	Volvo Powershift 6-speed (GFT) / 1161838/1161839
VW (Audi, Seat, Skoda) 6-speed, VW/Audi TL 52529 (spec) / G 052 529 A2 or A6 (fluid), VW/Audi TL 521 82 (spec) / G 052 182 A2 or A6 (fluid), VW G 055 529	ZF/Porsche Oil #999.917.080.00
MB 236.21	

# **AQDCT Plus**

## Fully Synthetic

#### **Product Features:**

- High performance DCT fluid for use in the widest range of vehicle makes fitted with DSG or DCT wet transmissions
- Provides excellent friction durability, scuffing protection and fatigue resistance
- To ensure correct oil selection check Comma's latest Application guide in store or online at CommaOil.com

### Handling:

- Avoid extremes of temperature
- Product in cardboard cartons must be stored under cover and away from damp conditions
- Barrels should be stored under cover if possible
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs

#### **Shelf Life:**

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight diget code printed on the bottle. YYYY.MM.DD.

#### Pack Size Availability:

- 1L
- 5L
- 20L

Typical Inspection Data are typical of those obtained with normal production tolerance and do not constitute a specification. Variations that do not affect product performance are to be expected during normal manufacture and at different blending locations. The information contained herein is subject to change without notice. All products may not be available locally. For more information, contact your local Cosan contact or visit www.CommaOil.com.

**UPDATED: 11-12-2019**