



## Typical Inspection Data:

Colour	Copper
Copper Content	8.5 %wt
Texture	Smooth
Thickener	Bentonite
Unworked Penetration @ 25°C	285 mm/10
Operating Temperature Range	-40°C to 1150°C
Drop Point	Infusible

## Copper Ease

### Product Features:

- Anti-seize assembly compound with extreme temperature tolerance (-40 °C to +1150 °C).
- Forms a dense protective coating over metal parts - will not wash or burn off.
- Helps prevent brake disc squeal when applied to the back of brake pads.
- Improves sealing and eases assembly and dismantling of:
  - o Cylinder head gaskets and bolts
  - o Gaskets of all descriptions
  - o Steering and suspension
  - o Universal joints
  - o Spark plugs
  - o Nuts and bolts
  - o Exhaust systems
- Suitable for automatic and individual applications

### Directions for use:

- Clean all surfaces before application.
- To prevent disc squeal: apply directly to callipers and back of disc pad.
- Warning: Do not apply to friction material or disc.

### Handling:

- Store under cover.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

### Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 30-03-2021