



Typical Inspection Data:

Density @ 20°C	0.843 g/cm ³
Viscosity @ 100°C	9.5 cSt
Viscosity @ 40°C	50 cSt
Viscosity Index	177
Viscosity CCS @ -35°C	5900 cP
T.B.N.	10.7 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.08%
Calcium	0.11%
Phosphorus	0.08%
Colour	Brown
Flash Point	>210°C
Pour Point	-48°C

Eco-P 0W-30

Fully Synthetic

Recommended by Comma for applications requiring:

PSA B71 2312
ACEA C2

Product Features:

- Fully synthetic, high performance fuel-economy promoting engine oil, developed specifically for modern petrol and diesel PSA engines.
- To ensure correct oil selection use Comma's latest application guide instore or online at www.CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 05-06-2023